

resolve series

food service

R6027



**santec**<sup>®</sup>  
clean needs. met.™



# twenty five

high foaming chlorinated caustic cleaner

limpiador cáustico colorado de espumación

resolve series | high-performance food service solutions

**twenty five** is a heavy duty, foaming, chlorinated liquid alkaline cleaner. Twenty Five contains a blend of biodegradable synthetic detergents, foam stabilizers, alkaline builders, water softeners, and chlorine. For use on all types of non-porous metal surfaces, including aluminum and galvanized.

## directions for use

**FOR FOAM CLEANING:** Mix 2 to 5 ounces per gallon of hot water. Apply as a foam to all surfaces. Allow contact time of 5 to 10 minutes and scrub thoroughly with brush. Do not allow solution to dry. Rinse all surfaces thoroughly. **FOR MEDIUM-DUTY STEAM CLEANING:** Dilute 2 to 6 ounces per gallon of water and apply with a steam cleaner. Rinse thoroughly with water. **FOR HIGH PRESSURE WASHING:** Dilute 2 to 4 ounces per gallon of water and apply with pressure sprayer. Rinse surfaces thoroughly with water.

### WARNING

#### HAZARD STATEMENTS

Causes severe skin burns and eye damage.

May be corrosive to metals.

#### PRECAUTIONARY STATEMENTS

Wear protective gloves, splash goggles, face shield, full suit, vapor respirator and boots.

Do not breathe mist /vapors /spray.

Wash thoroughly after handling.

#### FIRST AID

Eye Contact: Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately. Skin Contact: Wash skin with copious amount of water. Seek medical attention immediately. Inhalation: Remove to fresh air. Seek medical attention immediately. Ingestion: Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.



### STORAGE

Store in original container protected from sunlight, well ventilated area, away from incompatible materials, food and drink. Keep out of reach of children.

#### SPILL /LEAK

Avoid runoff into storm sewers and ditches which leads to waterways. Absorb spillage with an inert dry material and place in an appropriate waste disposal container.

#### DISPOSAL

Dispose of material in accordance with local, state and federal regulations.

#### HAZARDOUS INGREDIENTS

Potassium Hydroxide (1310-58-3)

Sodium Hydroxide (1310-73-2)

Sodium Hypochlorite (7681-52-9)

**santec**<sup>®</sup>  
clean needs. met.™

Toll-Free 888-726-8323

Offices 908-912-2500

Emergency 800-424-9300

[www.cleaneeds.com](http://www.cleaneeds.com)



4 0 2 7